

CLASS 1

Building Product Information Sheet

Product name:				
FAR 3-Way DHW Valve Kit				
Product line (the product line	e from which the product is customised):			
Zone Valves				
Product description and its in	ntended use (measurements, materials, usage):			
Product description and its intended use (measurements, materials, usage): Brass Control valve for diverting to coils of hot water cylinder. Male/Male connections. Includes unions.				
Requires electrical actuation, and so is a electrical appliance.				
male/male/male thr	read in 1" for 10 and 16kW heatpumps.			
male/male/male thread in 1 $\frac{1}{4}$ " (32mm) for 16kW heatpumps and above.				
Not for use with potable water.				
Draduct identifier (if applied	blak			
Product identifier (if applicated HPKVK3, HPKVK2	oie).			
111 10 10 111 10 112				
Please of manufacturer:	Aotearoa New Zealand			
Legal and trading name of th	ne manufacturer(s):			
Far Rubinetterie SpA				
Legal and trading name of th	ne manufacturer(s):			
Central Heating New Zealand Ltd				
Address for service:				
STREET NAME 52 Pilkington	Way SUBURB Wigram			
CITY, COUNTRY Christchurch, New Zealand POSTCODE 8042				
Website:	https://www.centralheating.co.nz/			
Email Address:	info@centralheating.co.nz			
Phone No. (if applicable):	03 357 1233			
NZBN (if applicable):	9429036621231			



Relevant Building Code clauses:

Clause B2 DURABILITY:	Clause	В2	DUR/	ABIL	ITY:
-----------------------	--------	----	------	-------------	------

Performance B2.3.1 (b)

Clause F2 HAZARDOUS BUILDING MATERIALS:

Performance F2.3.1.

Clause G10 PIPED SERVICES:

Performance G10.3.1 (a).

Statement on how the building product is expected to contribute to compliance:

Clause B2 DURABILITY:

Performance B2.3.1 (b) 15 years. Valves are moderately easy to access and replace if installed in accordance with the instructions and product requirements.

Clause F2 HAZARDOUS BUILDING MATERIALS:

Performance F2.3.1. Control valves meet this requirement and do not present a health hazard to people.

Clause G10 PIPED SERVICES:

Performance G10.3.1 (a). Heating valves are supplied by a non-potable piping system, which contributes to meeting this requirement when used in heating systems.

- options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)
- standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured.
- physical properties of the building product
- how the building product is intended to be used.

Limitations on the use of the building product:

Please refer to the FAR 3-way DHW valve <u>technical information</u> provided on the Central Heating NZ website.

The hot water heating system must not be connected to the potable water supply system.

valve is not suitable for potable water supply.

Design requirements that would support the use of the building product:

The heating system design, including the layout of the pipe, must be carried out by a suitably qualified designer.

Please refer to the FAR 3-way DHW valve <u>technical information</u> provided on the Central Heating NZ website.

Design must consider the requirement of building code clause H1 for pipework and heating design.

Installation requirements:

Date:

Please refer to the FAR 3-way DHW valve <u>technical information</u> and installation instructions provided on the Central Heating NZ website.

The system installation must be carried out by a licensed and qualified tradesperson, in accordance with the design supplied by the suitably qualified designer.

A detailed as-built plan and site photos shall be provided upon the conclusion of installation showing location of all associated pipework and the valve location on a heating schematic.

From technical installation sheet:

Before fitting the actuator (HPKVK3), make sure that the markings on the valve body shaft correspond with the position as shown (in the installation instructions). The symbol on the right of the slot indicates the heating side of the valve.

The actuator should be in the position shown to allow alignment with the valve body receiver slot. It can go in either orientation as shown in the installation instructions.

Maintenance requirements:
Is the building product/building product line subject to warning or ban under section 26:
☐ Yes ⊠ No
If yes, description of the warning or ban under section 26:

3 0 0 8 2 3

3